

### T1805

- Analogue Earth Resistance Tester
- Large display
- Taut band movement
- 2 and 3 Wire tester



CAT III 150V

#### Technical Overview

Feature	Parameter	Accuracy
Earth Resistance ( $\Omega$ )	Resistance: 10, 100, 1.000 $\Omega$	$\pm 2.5\%$ of full scale
Earth Voltage (V)	30V AC (5k $\Omega$ /V)	$\pm 1\%$ of full scale
Measuring System	Resistance: (Constant current inverter 820Hz approx, 2mA) Voltage: rectifier type 0 - 30V AC, 40-500Hz	
Withstand Voltage	1.500V AC (one minute)	$\pm 1.8\%$ + 4 Digit

#### Model Specification

Power Source	8 x 1.5V AA Batteries
Standard Accessories	Test Leads (Lengths: Red - 1m and 15m, Yellow - 10m, Green - 5m) Earth Spikes, Shoulder Belt, <b>TAL36</b> (P57)
Certificates	UL, IEC61010-1. Certificate of Conformance*

\* Calibration performed with supplied test leads

Johannesburg  
Tel: (011) 879-6620

Cape Town  
Tel: (021) 594-7100

Durban  
Tel: (031) 492-0481

Port Elizabeth  
Tel: (041) 408-2400

