



TBM807

- Electrician's
- Beep guard
- Data hold
- Frequenc
- Min/Max
- Relative zero
- Capacitanc

Technical Overview

Feature	Parameter	Accuracy
DC Voltage (V)	400mV, 4, 40, 400, 1000V	±1.0% + 4 Digit
AC Voltage (V)	400mV, 4, 40, 400, 1000V	4 -400V ±1.5% + 5 Digit, 1000V ±4.0% + 5 Digit
DC Current (A)	400μ, 4000μ, 40mA, 400mA, 4.10A	±1.2% + 3 Digit
AC Current (A)	400μ, 4000μ, 40mA, 400mA, 4.10A	±1.8% + 4 Digit
Resistance (Ω)	400, 4k, 40k, 400k, 4M, 40MΩ	±2.0% + 4 Digit
Temperature (°C)	-20°C to 300°C	±2.0% + 3°C
Capacitance (F)	500nF, 5μ, 50μ, 500μ, 3000μF	±3.5% + 6 Digit
Frequency (Hz)	50, 500, 5k, 50k, 500k, 1MHz	±0.5% + 4 Digit
Counts	3 -3/4 Digits	4000 Counts



CAT III 600V

Model Specification

Power Source	2 x 1.5V AAA Batteries
Standard Accessories	Temp Probe TBMTEMPPROBE
Certificates	UL, IEC61010-1. Certificate of Conformance

Johannesburg
Tel: (011) 879-6620

Cape Town
Tel: (021) 594-7100

Durban
Tel: (031) 492-0481

Port Elizabeth
Tel: (041) 408-2400

