



TBM135 1000A AC

- Jaw size: 45mm
- Data Logging
- 5400 Point logging
- Continuity

Technical Overview

Feature	Parameter	Accuracy
AC Current (A)	40, 400, 1000A	2.0% + 5 Digit
DC Voltage (V)	600V	0.5% + 5 Digit
AC Voltage (V)	600V	1.5% + 5 Digit
Resistance (Ω)	999.9Ω	1.0% + 6 Digit
Temperature (°C)	-50 to 300°C	
Frequency (Hz)	5 to 500Hz	±0.5% + 4 Digit
Thd%-r	0.0%~99.9%	Fundamental 1% + 6 Digit 2~3 Harmonics 5% + 6 Digit 4~51 St Harmonics 2%
Counts	3 -5/6 Digits	6000 Counts



CAT III 300V

Model Specification

Power Source	2 x 1.5V AAA Batteries
Standard Accessories	Carry Pouch, Type-K Thermocouple
Optional Accessories	RS232 Cable and Software TBU13X, Adaptor (P14)
Certificates	UL, IEC61010-1. Certificate of Conformance

Johannesburg
Tel: (011) 879-6620

Cape Town
Tel: (021) 594-7100

Durban
Tel: (031) 492-0481

Port Elizabeth
Tel: (041) 408-2400

