



### T2608 2000A DC/ 1500A AC

- Jaw size: 57mm
- Min/Max
- Data hold/Peak hold
- Auto power off
- Diode
- Continuity
- Bargraph

#### Technical Overview

Feature	Parameter	Accuracy
DC Current (A)	400, 2000A	±1.5% + 5 Digit
AC Current (A)	400, 1500A	±1.5% + 5 Digit
DC Voltage (V)	400mV, 4, 40, 400, 1000V	±0.5% + 1 Digit
AC Voltage (V)	400mV, 4, 40, 400, 750V	±1.5% + 4 Digit
Resistance (Ω)	400, 4k, 40k, 400k, 4M, 40MΩ	±1.0% + 4 Digit
Frequency (Hz)	10, 1k, 10k, 100k, 400kHz	±0.1% + 4 Digit
Capacitance (F)	4nF, 40nF, 400nF, 4μ, 40μF	±1.0% + 4 Digit
Counts	3 -3/4 Digits	4000 Counts



CAT III 1000V

#### Model Specification

Power Source	1 x 9V Battery
Certificates	UL, IEC61010-1. Certificate of Conformance

Johannesburg  
Tel: (011) 879-6620

Cape Town  
Tel: (021) 594-7100

Durban  
Tel: (031) 492-0481

Port Elizabeth  
Tel: (041) 408-2400

