



### TBM062 400A AC/DC

- Jaw size: 30mm
- Diode
- Continuity
- Relative zero
- Auto power off
- Backlit

#### Technical Overview

Feature	Parameter	Accuracy
DC Current (A)	0.01, 400A	±2.5% + 5 Digit
AC Current (A)	0.01, 400A	±2.5% + 5 Digit
DC Voltage (V)	400mV, 4, 40, 400, 600V	±1.0% + 4 Digit
AC Voltage (V)	4, 40, 400, 600V	1.5% + 5 Digit
Resistance (Ω)	400, 4k, 40k, 400k, 4M, 40MΩ	4k, 40k, 400kΩ ±0.6% + 4 Digit, 4MΩ ±1.0% + 4 Digit, 40MΩ ±2.0% + 4 Digit
Frequency (Hz)	1kHz to 100kHz	±2.0% + 4 Digit
Capacitance (F)	500nF, 5μ, 50μ, 500μ, 3000μF	±3.5% + 6 Digit
Counts	3 -3/4 Digits	4000 Counts

#### Model Specification

Power Source	2 x 1.5V AAA Batteries
Standard Accessories	Carry Pouch
Certificates	UL, IEC61010-1. Certificate of Conformance



CAT III 600V

Johannesburg  
Tel: (011) 879-6620

Cape Town  
Tel: (021) 594-7100

Durban  
Tel: (031) 492-0481

Port Elizabeth  
Tel: (041) 408-2400

