



### TBM3030 600A AC

- Jaw size: 26m
- Large LCD display
- Diode
- Continuity
- Relative zero
- Data hold

#### Technical Overview

Feature	Parameter	Accuracy
AC Current (A)	40, 600A	±1.9% + 8 Digit
AC Voltage (V)	4, 40, 400, 600V	4.40, 400V ±1.5% + 5 Digit, 600V ±2.0% + 5 Digit
DC Voltage (V)	400mV, 4, 40, 400, 600V	±1.0% + 4 Digit
Resistance (Ω)	400, 4k, 40k, 400k, 4M, 40MΩ	4k, 40k, 400kΩ ±0.6% + 4 Digit, 4MΩ ±1.0% + 4 Digit, 40MΩ ±2.0% + 4 Digit
Capacitance (F)	500nF, 5μ, 50μ, 500μ, 3000μF	±3.5% + 6 Digit
Frequency (Hz)	5Hz to 100kHz	±0.5% + 4 Digit
Counts	3 -3/4 Digits	4000 Counts

#### Model Specification

Power Source	1 x 3V Battery CR2032
Standard Accessories	Carry Pouch
Certificates	UL, IEC61010-1. Certificate of Conformance

CAT III 300V

Johannesburg  
Tel: (011) 879-6620

Cape Town  
Tel: (021) 594-7100

Durban  
Tel: (031) 492-0481

Port Elizabeth  
Tel: (041) 408-2400

