



T48

- Electronic
- Backlit
- Capacitance
- Inductance
- Frequency

Technical Overview

Feature	Parameter	Accuracy
DC Voltage (V)	200mV, 2, 20, 200, 1000V	±0.5% + 3 Digit
AC Voltage (V)	200mV, 2, 20, 200, 750V	±0.8% + 5 Digit
DC Current (A)	20µA, 200µA, 20mA, 200mA, 2A, 20A	±0.8% + 3 Digit
AC Current (A)	200mA, 20A	±1.0% + 5 Digit
Resistance (Ω)	200, 2k, 200k, 2M, 20M, 2000MΩ	±0.8 % + 3 Digit
Frequency (Hz)	2K, 200kHz	±0.5% + 4 Digit
Temperature (°C)	-20°C to 1000°C	±1.0% + 4 Digit
Capacitance (F)	20nF, 200nF, 2µF, 20µF, 200µF	20nF-20µF ±2.5% +20 Digit
Counts	3 -1/2 Digits	1 999 Counts

Model Specification

Power Source	1 x 9V Battery
Standard Accessories	Temp Probe TBMTEMPROBE

Johannesburg
Tel: (011) 879-6620

Cape Town
Tel: (021) 594-7100

Durban
Tel: (031) 492-0481

Port Elizabeth
Tel: (041) 408-2400

