



TBM061 400A AC/DC

- Jaw size: 30mm
- Diode
- Continuity
- Relative zero
- Auto power off

Technical Overview

| Feature | Parameter | Accuracy |
|-----------------|------------------------------|---|
| DC Current (A) | 0.01, 400A | ±2.5% + 5 Digit |
| AC Current (A) | 40.01, 400A | ±2.5% + 5 Digit |
| DC Voltage (V) | 400mV, 4, 40, 400, 600V | ±1.0% + 4 Digit |
| AC Voltage (V) | 4, 40, 400, 600V | 4, 40, 400V ±1.0% + 4 Digit, 600V ±2.0% + 4 Digit |
| Resistance (Ω) | 400, 4k, 40k, 400k, 40MΩ | 4k, 40k, 400kΩ ±0.6% + 4 Digit, 4MΩ ±1.0% + 4 Digit, 40MΩ ±2.0% + 4 Digit |
| Frequency (Hz) | 1kHz to 100kHz | ±2.0% + 4 Digit |
| Capacitance (F) | 500nF, 5μ, 50μ, 500μ, 3000μF | ±3.5% + 6 Digit |
| Counts | 3 -3/4 Digits | 4000 Counts |

Model Specification

| | |
|----------------------|--|
| Power Source | 2 x 1.5V AAA Batteries |
| Standard Accessories | Carry Pouch |
| Certificates | UL, IEC61010-1. Certificate of Conformance |

CAT III 600V

Johannesburg
Tel: (011) 879-6620

Cape Town
Tel: (021) 594-7100

Durban
Tel: (031) 492-0481

Port Elizabeth
Tel: (041) 408-2400

