



### TBM076 600A AC

- Jaw size: 30mm
- Amptip™
- 3-Phase rotation for mains and motor
- Non-contact EF detection
- DC  $\mu$ A - HVAC flame sensor via probe
- Rotary selector switch
- Continuity
- Data Hold

#### Technical Overview

Feature	Parameter	Accuracy
AC Current (A)	40, 600A	$\pm 1.8\% + 5$ Digit
DC Voltage (V)	400mV, 4, 40, 400, 600V	$\pm 1.0\% + 5$ Digit
AC Voltage (V)	4, 40, 400, 600V	440, 400V $\pm 1.5\% + 5$ Digit, 600V $\pm 1.2\% + 7$ Digit
Resistance ( $\Omega$ )	600, 6k $\Omega$ , 60k $\Omega$	600k $\Omega$ , 6k $\Omega$ , 60k $\Omega$ , $\pm 1.0\% + 5$ Digit
Temperature ( $^{\circ}$ C)	-40 $^{\circ}$ C to 400 $^{\circ}$ C	$\pm 1\%$ - 0.8 $^{\circ}$ C, 100 $^{\circ}$ C - 400 $^{\circ}$ C $\pm 1.0\%$ - 1 $^{\circ}$ C
Frequency (Hz)	5Hz to 100kHz	$\pm 0.5\% + 4$ Digit
Capacitance (F)	200 $\mu$ , 2500 $\mu$ F	$\pm 2\% + 4$ Digit
Counts	3 -5/6 Digits	6000 Counts



CAT IV 300V

#### Model Specification

Power Source	2 x 1.5V AAA Batteries
Standard Accessories	Carry Pouch, Temp Probe TBMTEMPROBE
Certificates	UL, IEC61010-1. Certificate of Conformance

Johannesburg  
Tel: (011) 879-6620

Cape Town  
Tel: (021) 594-7100

Durban  
Tel: (031) 492-0481

Port Elizabeth  
Tel: (041) 408-2400

